

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME	Sheet	1 of 5
	Revision No.	0
ROLCER TURBO D-ZEL TX 25W-50	Last Revision	
	Issue Date	15-09-2020

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Trade Name	ROLCER TURBO D-ZEL TX 25W-50
Manufacturer's/Supplier's Name	Universal Projects Factory for Petroleum Products
Street Address	Office No. 618, Akharia Building 2, Olaya
City	Riyadh, Kingdom of Saudi Arabia
P. O. Box	58704
Emergency Telephone No.	+966 11 4191741

#### SECTION 2: COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Components</u>	<u>Weight %</u>
Highly refined Mineral Base Oils	>85
Performance Additives	<15

#### **SECTION 3: HAZARDOUS IDENTIFICATION**

Emergency Overview

May cause eye irritation May cause an allergic skin reaction

#### Potential Health Effects

Eyes The eye irritation potential of this substance has not been determined.

- Skin This substance may cause skin irritation on prolonged or frequently repeated contact. The skin sensitization potential of this product has not been determined. The systemic toxicity of this substance has not been determined. However, it should be practically non-toxic to internal organs if it gets on the skin.
- Inhalation The systemic toxicity of this substance has not been determined. However, it should be practically non-toxic to internal organs if inhaled.

Ingestion If swallowed, this substance is considered practically non-toxic to internal organs. (See Section XI for Toxicological Information)



# مصنع عالمية المشاريع للمنتجات البترولية UNIVERSAL PROJECTS FACTORY FOR PETROLEUM PRODUCTS

PRODUCT NAME	Sheet	2 of 5
	Revision No.	0
ROLCER TURBO D-ZEL TX 25W-50	Last Revision	
	Issue Date	15-09-2020

## **SECTION 4: FIRST AID MEASURES**

Eye Contact	Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing and continue flushing for at least 15 minutes. Get medical attention if irritation persists.
Skin Contact	No specific first aid measures are required because this material is not expected to be harmful if it contacts the skin. As a precaution, remove clothing and shoes if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing and shoes before reuse.
Inhalation	No specific first aid measures are required because this material is not expected to be harmful if inhaled. If exposed to excessive levels of material in the air, move the exposed to fresh air. Get medical attention if coughing or respiratory discomfort occurs.
Ingestion	If swallowed, give water or milk to drink and telephone for medical advice. Consult medical personnel before inducing vomiting.

### **SECTION 5: FIRE FIGHTING MEASURES**

# Flammable Properties

Flash point ( <sup>0</sup> C) and Method Auto Ignition Temperature ( <sup>0</sup> C)	242 <sup>o</sup> C (COC), Typical Value Not Estimated
Flammability Limits	
Upper Explosive Limit (% Vol)	Not applicable
Lower Explosive Limit (% Vol)	Not applicable
Extinguishing Media	Carbon Dioxide, Foam, Dry Chemical and Water Fog
Combustion Products	Normal combustion forms carbon dioxide and water vapour and may produce oxides of sulfur and phosphorus. Incomplete combustion can produce carbon monoxide.
Fire Fighting Instructions TDG Flammability	For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.



PRODUCT NAME	Sheet	3 of 5
	Revision No.	0
ROLCER TURBO D-ZEL TX 25W-50	Last Revision	
	Issue Date	15-09-2020

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Accidental Release Measures

Stop the source of the leak or release. Clean up release as soon as possible. Contain liquid to protect further contamination of soil, surface water or ground water. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.

#### **SECTION 7: HANDLING AND STORAGE**

Do not weld, heat or drill container. Replace cap or bung. Emptied container still contains material which may ignite with explosive violence if heated sufficiently. Avoid contact with eyes, skin and clothing.

Storage Requirements Keep container closed to avoid contamination with moisture or water.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use closed system where possible to avoid eye and skin exposure.

Personal Protective Equipment

Eyes	Wear chemical goggles
Skin	Avoid contact with skin or clothing. Skin contact should be minimized by wearing
	protective clothing including gloves.
Inhalation	If operating conditions result in airborne mists or vapours of this material, the use of
	an approved respirator is recommended.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Odour/Appearance	Clear & Bright liquid
Form	Liquid
Boiling Point	Not applicable
Vapour Density	Not applicable
Density @ 15.6 °C, Kg/L	0.89 (Typical Value)
Pour Point <sup>o</sup> C	-24 (Typical Value)
Solubility (Water)	Negligible
Viscosity, cSt	18.7 @ 100 °C (Typical Value)



# مصنع عالمية المشاريع للمنتجات البترولية UNIVERSAL PROJECTS FACTORY FOR PETROLEUM PRODUCTS

PRODUCT NAME	Sheet	4 of 5
	Revision No.	0
ROLCER TURBO D-ZEL TX 25W-50	Last Revision	
	Issue Date	15-09-2020

## SECTION 10: STABILITY AND REACTIVITY

Conditions to avoid	No data available
Chemical stability	Stable
Hazardous decomposition products	No data available
Incompatibility with other substances	May react with strong oxidizing agents
Hazardous polymerization	Polymerization will not occur

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### Additional Toxicological Information

This product contains petroleum base oils which may be refined by various process including severe solvent extraction, severe hydrocracking or severe hydrotreating. None of the oils require a cancer warning under OSHA, NTP and IARC.

Eyes	Practically non-irritating
Skin	Practically non-irritating
Oral Toxicity	No product toxicology data available
Inhalation	Do not cause respiratory irritation
SECTION 12: ECOLOGICAL INFORMATION	
Eco Toxicity	Poor soluble mixture. Practically non-toxic to aquatic organisms.
Biodegradation	No data available

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Place contaminated materials in disposable containers and dispose off in a manner consistent with applicable regulations. Contact local environmental or health authorities for disposal of this material.

Do not weld, heat or drill container. Replace cap or bung. Emptied container still contains material which may ignite with explosive violence if heated sufficiently.



# مصنع عالمية المشاريع للمنتجات البترولية UNIVERSAL PROJECTS FACTORY FOR PETROLEUM PRODUCTS

PRODUCT NAME	Sheet	5 of 5
ROLCER TURBO D-ZEL TX 25W-50	Revision No.	0
	Last Revision	
	Issue Date	15-09-2020

#### **SECTION 14: TRANSPORT INFORMATION**

General Information

Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes

#### **SECTION 15: REGULATORY INFORMATION**

Not Applicable

#### **SECTION 16: OTHER INFORMATION**

#### DISCLAIMER

The data and information contained herein are being furnished for informational purposes only, upon the express condition that each customer shall make its own assessment of appropriate use, appropriate shipping, transfer and storage of materials manufactured by Universal Projects Factory for Petroleum Products. Although based on information sources it is considered to be accurate and reliable, Universal Projects Factory for Petroleum Products makes no warranty, either express or implied, including any warranties of merchantability or fitness for a particular purpose regarding the validity of this information, the information sources upon which the same are based, or results to be obtained, and expressly disclaims liabilities for damages or injuries resulting from the use thereof.