

SynTrack FX

Fully Synthetic Premium Petrol Engine Oil

Technical Data Sheet

Product Description

Rolcer SynTrack FX is a fully synthetic premium high performance multigrade petrol engine oil for superior performance and fuel efficiency. This product is intended for modern generation high performance passenger cars including turbocharged/supercharged engines, hybrid engines and naturally aspirated engines. Its superior formula provides exceptional thermal and oxidation stability, outstanding protection to engine components against wear and corrosion and keeps the engine clean.

Performance Specification

Rolcer SynTrack FX meets or exceeds the following performance requirements:

- API SP
- ILSAC GF-6A Resource Conserving (SAE 5W-20 & SAE 5W-30)

Features/Benefits

- SAE 5W-20, SAE 5W-30, SAE 5W-40 and SAE 10W-40
- Protects the engine by minimizing friction and wear at start-up
- Optimizes fuel economy
- Provides wear protection and reduces emissions
- Keeps the engine clean from sludge
- Ensures longer oil drain intervals
- Suitable for American, European and Japanese vehicles

Typical Properties

Test Parameters	ASTM Method	Typical Values			
		SAE 5W-20	SAE 5W-30	SAE 5W-40	SAE 10W-40
Density @ 15 ^o C, Kg/L	D4052	0.837	0.878	0.852	0.856
Kinematic Viscosity at 100 ^o C, cSt	D445	8.61	11.14	14.2	14.3
Viscosity Index	D2270	152	165	175	156
Total Base Number mg KOH/gm	D2896	8	8	8	8
Pour Point ^o C	D97	-42	-38	-40	-34
Flash Point (COC), ^o C	D92	225	223	222	225

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

UNIVERSAL PROJECTS FACTORY FOR PETROLEUM PRODUCTS