

Turbo D-Zel TX

High Performance Diesel Engine Oil

Technical Data Sheet

Product Description

Rolcer Turbo D-Zel TX is high performance diesel engine oil formulated from highly refined quality base oils and an advanced additive package. It is suitable for older generation turbocharged/supercharged automobile, heavy duty industrial and off-highway diesel engines.

Performance Specification

Rolcer Turbo D-Zel TX meets or exceeds the following performance requirements:

- API CH-4

Features/Benefits

- SAE 20W-50 & 25W-50
- Suitable for use in diesel engines requiring API CH-4 lubricant performance
- Excellent soot control and maintains engine cleanliness
- Blended to ensure fuel efficiency and reduced oil consumption
- Outstanding anti-wear properties for protecting heavy loaded engine parts
- Processed from premium quality virgin base oils and performance additives
- Excellent thermal and oxidation stability

Typical Properties

Test Parameters	ASTM Method	Typical Values	
		SAE 20W-50	SAE 25W-50
Density @ 15.6 ⁰ C, Kg/L	D1298	0.88	0.89
Kinematic Viscosity at 100 ⁰ C, cSt	D445	18.8	18.7
Viscosity Index	D2270	121	129
Total Base Number mg KOH/gm	D2896	11	11
Pour Point ⁰ C	D97	-27	-24
Flash Point (COC), ⁰ C	D92	232	242

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

UNIVERSAL PROJECTS FACTORY FOR PETROLEUM PRODUCTS